

I active



I ACTIVE

Interactive Flat Panel Premium Series



www.iactive.co.in

Interactive Flat Panel

Iactive Interactive flat panel provides clear 4K UHD resolution with dual operating system Android and Windows built in. Iactive Interactive flat panel delivers incredible experience for both Classroom & meeting places with built in annotation capability, screen mirroring and 40 touch points. The built in software enables users to sync their personal devices like laptop, desktop, palmtop, mobile etc... with the Iactive IFP users can share content and take control, Iactive premium interactive flat panel series available with different screen sizes **65, 75, 86** and **98** inches.

Iactive 18 series



- 4k Ultra HD Display
- Eye Protection
- Zero Gap Bonding Technology
- Wireless Projection
- One Network Support, Android And Ops Both On Gigabit Network
- Ultra - Narrow Bezel Design
- Split Screen
- ± 1 mm High Precision Infrared Touch Control
- Supports Dual Pens And Dual Colour Displays
- 7mm Anti-Glare Toughened Glass With High Haze OC For Clear Display Against Ambient Light Interference

Iactive 18 series Plus

- 4k Ultra HD Display
- Eye Protection
- Zero Gap Bonding Technology
- Wireless Projection
- One Network Support, Android And Ops Both on Gigabit Network
- Ultra - Narrow Bezel Design
- Split Screen
- ± 1 mm High Precision Infrared Touch Control
- Supports Dual Pens And Dual Colour Displays
- 4k Camera 13mp With 6 Array Mic Built In
- 7mm Anti-glare Toughened Glass With High Haze OC For Clear Display Against Ambient Light Interference



I active

OPS

(Open Pluggable System)

Specially designed for AiO
Interactive Flat Panel Displays

8th Generation

Core i5,i7 / 8GB RAM / 256GB SSD

10th Generation

Core i5,i7 / 8GB RAM / 256GB SSD

11th Generation

Core i5,i7 / 8GB RAM / 256GB SSD



Windows 11 OS
Compatible



intel inside



Support OPS
Expansion



USB Type C
Connection



Wi-Fi
Connectivity



Multiple
Ports

I ACTIVE IFPD STAND

Supports your various workplace, heavy duty panel
stand for 65,75,86 & 98 inch panels.



www.iactive.co.in

MODEL		IFP65018/75018/86018 PLUS	IFP65018/75018/86018	IFP65016/ 75016/86016 PLUS	
Display Parameter	Visual Ratio	16:09			
	Resolution	3840 (H) ×2160 (V)			
	Frequency	60Hz			
	Display Colors	1.07B (10bit)			
	Color saturability	72%			
	Contrast ratio(Typ)	10000:1		10000:1	
	Viewing Angle	178° (H/V)			
	Light source	DLED			
	Brightness	450cd/m2		400cd/m2	
	Thickness	7mm		7mm	
Life Span	≥60000		≥50000hrs		
Audio Video	Speaker	2			
	Soundtrack	2×16W + Booster Equalizer		2×16W	
Touch Parameter	Touch specifications	Non-contact infrared sensing technology		Infrared identification	
	Support Systems	Windows10/11/Android/Linux/Mac OS X/Chrome			
	Touch Points	40 Points Touch		20 points touch	
	Min.Identifier	2mm			
	Input mode	Opaque object (finger, pen, etc.)			
	Response time	≤8ms			
	Touch depth	±1mm			
	Writing height	≤3mm			
	Writing display	Single Stylus pen two-colour		Opaque object (finger, pen)	
System	System Version	Android 11.0		Android 11.0	
	CPU	Quad Core A55 4Core		Quad Core A55 4Core	
	GPU	Mali G52MP2		Mali G52MP2	
	RAM	4GB			
	ROM	32GB			
	Version	5			
Wireless	Bluetooth	Working Distance 0~10m			
	Wi-Fi	Version	802.11ac/b/g/n/a/ax		802.11ac
		Working Frequency	2.4GHz/5GHz		2.4GHz/5GHz
		Working Distance	0~10m		0~10m
		Remark	Via the wireless module SI07B		Built-in Wi-Fi mode
I/O Interface	HDMI IN	3 (on board 2, front 1)		2	
	HDMI OUT	1			
	USB 2.0	1		1	
	USB 3.0	4 (on board 2, front 2)		1	
	TOUCH	2 (on board 1, front 1)		1	
	VGA IN	1			
	AUDIO IN	1		1	
	AUDIO OUT	1		1	
	SPDIF	1		1	
	RS232	1		1	
	TYPE-C	1(front)			
	RJ45 OUT	1		1	
	RJ45 IN	1		1	
	Front Small Board Interface	2*USB3.0+TYPE-C+TOUCH OUT+HDMI IN		2* USB	
Power	Voltage	100-240V ~ 50/60Hz 4A		100-240V ~ 50/60Hz 4A	
	Max. Power Consumption	400W		400W	
	Standby Power Consumption	≤0.5W			
Accessories	Power Cord	×1			
	Stylus Pen	×2			
	Wall mount	×1			
	Operation Manual	×1			
Environment	Working Temperature	0℃~40℃			
	Working Humidity	10%~90%RH			
	Storage Temperature	-20℃~60℃			
	Storage Humidity	10%~90%RH			
	Working Elevation	<5000m			
Standard Module	Wi-Fi Module Model	SI07B	SI07B	Built-in Wi-Fi mode	
Optional Module	OPS Model	OPS42A	OPS42A	OPS42A	
Parameters	Camera	Pixel	13 Megapixel camera		
		Qty.	1		
		Location	Upper Frame		
		Viewing Angle	DFOV: 100° HFOV:91.9° VFOV:60		
	Microphone	Function	Support Autofocus, Auto White Balance, Backlight Compensation, 3d Noise Reduction		
		Pick-up distance	0~8m		
Qty.		6			
Pick-up angle		0°~180°			
Function	Supports Echo Cancellation, Background noise suppression, gain compensation				

Iactive Technology Pvt Ltd.
Blueskart E Commerce Pvt Ltd.
Corporate Office:
No 1148/1, 10th B Cross Rd,
West Of Chord Road 2nd Stage, Shankar Mutt,
2nd Floor Mahalakshampuram,
Karnataka, Bengaluru - 560 086.
e-mail: sales@iactive.co.in
Customer care: +91 63622 21522



www.iactive.co.in



Dealer Stamp: